



GPON ONT G-95K

Platform Briefing

VERSION1

Oct.2017

Partnership for the Next Generation Broadband CPE

www.cambridgeig.com

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.

■ Overview

To extend the GPON deployment in existing access network for business and residential subscribers, GPON ONT SFP G-95K provides the standard SFP package with SGMII interface, which can easily replace the Ethernet SFP module existing in Ethernet gateway, switch, router or backhaul equipment etc.

Equipped with ITU-T G.984 compliant GPON interface, G-95K incorporates interoperability, key customers' specific requirements and cost-efficiency. By integrating GPON MAC and standard compliant OMCI stack, G-95K provides all GPON functionality and full range FCAPS management features including supervision, monitoring and maintenance

■ Service

Data

The G-95K ONT is delivered with one SFP (Small Form-factor Pluggable) based 1000 Base-X Gigabit Ethernet data interface, supporting:

- Built-in layer-2 switching
- Advanced data features such as VLAN tag manipulation, classification, and filtering

■ Specification

Dimensions

- 82 mm x 14 mm x 12.5 mm (L x W x D)

Power Supply

- Power Consumption: < 2.5W
- Power saving mode supported

Working Environment

- case operating temperature: -40~+85 °C
- Humidity: 5 ~ 95% relative humidity, non-condensed

Safety & EMI

- CE compliant
- FCC/UL compliant

Installation

- SFP interface

GPON Interface

- Compliant with ITU-T G.984 GPON standards

- SFF type laser, SC/APC connector
- 1.244G bps Burst Mode Upstream Transmitter
- 2.488 Gbps Downstream Receiver
- Compliant with ITU-T G.984.2 Amd1, Class B+
 - APD receiver and DFB transmitter
 - 0.5~+5dBm launch power, -27 dBm sensitivity, and -8dBm overload
- Wavelengths:
 - US 1310nm, DS 1490nm
- Laser compliant with FCC 47 CFR Part 15, Class B, and FDA 21 CFR 1040.10 and 1040.11, Class I, ONT support Class C or Class C+ optics as an option

GPON QoS

- Multiple T-CONTs per device
- Multiple GEM Ports per device
- Flexible mapping between GEM Ports and T-CONT

- Activation with automatic discovered SN and password in conformance with ITU-T G.984.3
- AES-128 Decryption with key generation and switching
- FEC (Forward Error Correction)
- DBA reporting by piggyback reports in the DBRu (mode 0)
- 802.1p mapper service profile on U/S
- Mapping of GEM Ports into a T-CONT with priority queues based scheduling
- Support Multicast GEM port and incident broadcast GEM port.

Ethernet Interface

- SFP based 1000 Base-X GbE interface
- Hardware priority queues on the downstream direction in support of CoS
- 802.1D bridging
- Virtual switch based on 802.1q VLAN

- VLAN tagging/detagging
- VLAN stacking (Q-in-Q) and VLAN Translation
- IP ToS/DSCP to 802.1p mapping
- Class of Service based on VLAN-ID, 802.1p bit, ToS/DSCP
- Marking/remarking of 802.1p
- Broadcast/Multicast rate limiting

OAM

- Standard compliant OMCI (the embedded operations channel) interface as defined by ITU-T G.984.4 and G.988
- Alarming and AVC report, performance monitoring
- Remotely software image download over OMCI, as well as activation and rebooting
- Hold two software sets with software image integrity checking and automatic rollback

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.

■ Pin Description

PIN NO.	Name
1	VEET/BOOT4
2	TX_FAULT/ASC_TX/TOD
3	TX_DISABLE
4	SDA
5	SCL
6	MOD_ABS
7	Rate SEL/Dyinggasp
8	RX_LOS
9	VEET/1PPS
10	VEET/BOOT0
11	VEER
12	RD-
13	RD+
14	VEER
15	VCCR
16	VCCT
17	VEET
18	TD+
19	TD-
20	VEET

■ Enclosure

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.



■ Contact Information

Cambridge Industries USA Inc.

2445 Augustine Dr., 6th FL.

Santa Clara, CA 95054

Tel: +1(408)606-2200

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.

Email: nasales@cambridgeig.com

CIG Shanghai Co., Ltd.

5/F, Building 8, 2388 ChenHang Road

Shanghai, China 201114

Tel: +86-21-8023 3300

email: sales@cambridgeig.com

www.cambridgeig.com

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.