



GPON ONT G-200B1

Platform Briefing

VERSION3

Jan. 2018

Partnership for the Next Generation Broadband CPE

www.cigtech.com

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.

■ Overview

To deliver triple-play services to the subscriber in Fiber-to-the-Building or Fiber-to-the-Premises application, the GPON ONU G-200B1 for MDU (Multi-Dwelling Unit) incorporates interoperability, key customers' specific requirements and cost-efficiency.

Equipped with ITU-T G.984 compliant 2.5G Downstream and 1.25G Upstream GPON interface, the G-200B1 ONU supports the full Triple Play of services including voice, video (IPTV or VoD), and high speed internet access.

Compliant with standard OMCI definition, ONU G-200B1 is manageable at remote side and supports the full range FCAPS functions including supervision, monitoring, and maintenance.

■ Service

Data

The G-200B1 ONU is delivered with up to sixteen 10/100 Base-T Ethernet data interfaces, supporting:

- Auto-negotiation and MDI/MDIX auto-sensing
- Built-in layer-2 switch
- Advanced data features such as VLAN tag manipulation, classification, and filtering

Voice

To enable VoIP access, the G-200B1 ONT supports interfacing external IAD box or Home Router with voice capability through the Ethernet Interface.

Video

The G-200B1 ONU supports video contents delivered in the form of data (by multicast or unicast).

In case where multicast technology is used for delivering video contents through data channel, the ONT supports the dedicated multicast GEM port on the Downstream. So the video contents are received and processed by all the ONTs through the unified channel and this greatly improves the bandwidth efficiency.

In addition, the ONT supports IGMP snooping function to be applied for further optimization. When IGMP snooping is enabled, the ONT monitors the member joining and leaving activities at the Ethernet service port, and then selectively delivers the multicast streams.

■ Interface

Product	10/100 Base-T interface
G-200B1	16

■ Specification

Dimensions

- 440mm x220mm x 44mm (W x D x H, without bracket)
- 483mm x220mm x 44mm (W x D x H, with bracket)

Power Supply

- 3-PIN AC Power Connector
- Grounding Conductor
- Dying Gasp support
- Power Consumption: less than 22W

Working Environment

- Temperature: -10°C ~ 55°C
- Humidity: 5% ~ 95% relative humidity

Safety & EMI

- CE certificate
- FCC/UL compliant
- Lightning Protection:
 - Instant Surge 4 KV for power interface
 - Instant Surge 1.5 KV for user interface

Environmental Directive

- WEEE, RoHS6

Installation

- Rack mounting & Wall mounting

GPON Interface

- Compliant with ITU-T G.984 GPON standards
- SFF type laser, SC/APC connector
- CIG patented BoSA on board optical solution
- 1.244 Gbps Burst Mode Upstream Transmitter
- 2.488 Gbps Downstream Receiver
- Compliant with ITU-T G.984.2 Amd1, Class B+
 - 0.5dBm ~+5dBm launch power, -27dBm sensitivity, and -8dBm overload
- Wavelengths:
 - US 1310nm, DS 1490nm

- Laser compliant with FCC 47 CFR Part 15, Class B, and FDA 21 CFR 1040.10 and 1040.11, Class I, ONT support Class C or Class C+ optics as an option
- Support G.984.5 Blocking Filter as an option

GPON QoS

- Multiple T-CONTs per device
- Multiple GEM Ports per device
- Flexible mapping between GEM Ports and T-CONT
- Activation with automatic discovered SN and password in conformance with ITU-T G.984.3
- AES-128 Decryption with key generation and switching
- FEC (Forward Error Correction) in both directions
- DBA reporting by piggyback reports in the DBRu (mode 0)
- 802.1p mapper service profile on U/S
- Mapping of GEM Ports into a T-CONT with priority queues based scheduling
- Support Multicast GEM port and incidental broadcast GEM port.

Ethernet Interface

- 10/100 Base-T interface with RJ-45 connectors
- Ethernet port auto negotiation or manual configuration
- MDI/MDIX automatically sense
- Hardware priority queues on the downstream direction in support of CoS
- 802.1D bridging
- Virtual switch based on 802.1q VLAN
- VLAN tagging/de-tagging per Ethernet port
- VLAN stacking (Q-in-Q) and VLAN Translation
- IP ToS/DSCP to 802.1p mapping
- Class of Service based on UNI, VLAN-ID, 802.1p bit, ToS/DSCP

- Marking/remarking of 802.1p
- IGMP v2/v3 snooping
- Broadcast/Multicast rate limiting

Management Interface

- 1 console interface
- 1 management interface
- 4 PIN ALARM input interface (support 3 alarms)

LED

- LED for System
 - POWER
 - ALARM
 - NET
 - MGMT
- LED for ETHERNET(per port)

- MODE
- LINK

OAM

- Standard compliant OMCI (the embedded operations channel) interface as defined by ITU-T G.988
- Provisioning all kinds of services including Ethernet etc.
- Alarming and performance monitoring
- Remotely software image download over OMCI, as well as activation and rebooting
- Hold two software sets with software image integrity checking and automatic rollback
- Local access interface for debugging and maintenance
-

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.

■ Enclosure



■ Contact Information

Cambridge Industries USA Inc.

2445 Augustine Dr., 6th FL.

Santa Clara, CA 95054

Tel: +1(408)606-2200

Email: nasales@cigtech.com

CIG Shanghai Co., Ltd.

5/F, Building 8, 2388 ChenHang Road

Shanghai, China 201114

Tel: +86-21-8023 3300

Email: sales@cigtech.com

www.cigtech.com

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.