



GPON ONT G-97S

Platform Briefing

VERSION3

Dec.2018

Partnership for the Next Generation Broadband Solution

www.cigtech.com

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.

■ Overview

To extend the GPON deployment in existing access network for business and residential subscribers, GPON ONT SFP G-97S provides the standard SFP package with SGMII interface, which can easily replace the Ethernet SFP module existing in Ethernet gateway, switch, router or backhaul equipment etc.

Equipped with ITU-T G.984 compliant GPON interface, G-97S incorporates interoperability, key customers' specific requirements and cost-efficiency. By integrating GPON MAC and standard compliant OMCI stack, G-97S provides all GPON functionality and full range FCAPS management features including supervision, monitoring and maintenance

■ Service

Data

The G-97S ONT is delivered with one SFP (Small Form-factor Pluggable) based 1000 Base-X Gigabit Ethernet data interface, supporting:

- Built-in layer-2 switching
- Advanced data features such as VLAN tag manipulation, classification, and filtering

■ Specification

Dimensions

- 82 mm x 14 mm x 12.5 mm (L x W x D)

Power Supply

- Power Consumption: < 2W

Working Environment

- case operating temperature: -40~+85 °C
- Humidity: 5 ~ 95% relative humidity, non-condensed

Safety & EMI

- CE compliant
- FCC/UL compliant

Installation

- SFP interface

GPON Interface

- Compliant with ITU-T G.984 GPON standards
- SFF type laser, SC/APC connector

- 1.244G bps Burst Mode Upstream Transmitter
- 2.488 Gbps Downstream Receiver
- Compliant with ITU-T G.984.2 Amd1, Class B+
 - APD receiver and DFB transmitter
 - 0.5~+5dBm launch power, -27 dBm sensitivity, and -8dBm overload
- Wavelengths:
 - US 1310nm, DS 1490nm
- Laser compliant with FCC 47 CFR Part 15, Class B, and FDA 21 CFR 1040.10 and 1040.11, Class I, ONT support Class C or Class C+ optics as an option

GPON QoS

- Multiple T-CONTs per device
- Multiple GEM Ports per device
- Flexible mapping between GEM Ports and T-CONT
- Activation with automatic discovered SN and

- password in conformance with ITU-T G.984.3
- AES-128 Decryption with key generation and switching
- FEC (Forward Error Correction)
- DBA reporting by piggyback reports in the DBRu (mode 0)
- 802.1p mapper service profile on U/S
- Mapping of GEM Ports into a T-CONT with priority queues based scheduling
- Support Multicast GEM port and incident broadcast GEM port.

Ethernet Interface

- SFP based 1000 Base-X GbE interface
- Hardware priority queues on the downstream direction in support of CoS
- 802.1D bridging
- Virtual switch based on 802.1q VLAN

- VLAN tagging/detagging
- VLAN stacking (Q-in-Q) and VLAN Translation
- IP ToS/DSCP to 802.1p mapping
- Class of Service based on VLAN-ID, 802.1p bit, ToS/DSCP
- Marking/remarking of 802.1p
- Broadcast/Multicast rate limiting

OAM

- Standard compliant OMCI (the embedded operations channel) interface as defined by ITU-T G.984.4 and G.988
- Alarming and AVC report, performance monitoring
- Remotely software image download over OMCI, as well as activation and rebooting
- Hold two software sets with software image integrity checking and automatic rollback

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.

■ Pin Description

PIN NO.	Name	Description
1	VEET1	Transmitter ground
2	TX Fault	Transmitter fault is internally tied to transmit ground. Or TOD (time of day) output
3	TX Disable	Transmit disable, This pin is tied to PHY low power mode
4	MOD_DEF2/SDA	Signal SDA(data) of the two-wire serial ID interface
5	MOD_DEF1/SCL	Signal SCL(clock) of the two-wire serial ID interface
6	MOD_DEF0	This pin is internally tied to transmit ground
7	R_SEL/RST	Dying gasp pin.
8	LOS/SD	Loss of signal indication
9	VEER1	Receiver ground. Or 1PPS output
10	VEER2	Receiver ground
11	VEER3	Receiver ground
12	RD_N	Differential receiver outputs. User to terminate to 100 Ω differential at host. AC coupled
13	RD_P	Differential receiver outputs. User to terminate to 100 Ω differential at host. AC coupled
14	VEER4	Receiver ground
15	VCCR	3.3V power
16	VCCT	3.3V power
17	VEET2	Transmitter ground
18	TD_P	Differential transmitter inputs. User to terminate to 100 Ω differential at host. AC coupled
19	TD_N	Differential transmitter inputs. User to terminate to 100 Ω differential at host. AC coupled
20	VEET3	Transmitter ground

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.

■ Enclosure



Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.

■ Contact Information

Cambridge Industries USA Inc.

2445 Augustine Dr., 6th FL.

Santa Clara, CA 95054

Tel: +1(408)606-2200

Email: nasales@cigtech.com

CIG Shanghai Co., Ltd.

5/F, Building 8, 2388 ChenHang Road

Shanghai, China 201114

Tel: +86-21-8023 3300

Email: sales@cigtech.com

www.cigtech.com

Notice:

CIG have the sole right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice, CIG has the final interpretation.